

# TECHNICAL FEATURES

	Engine	Fuel	Starter	Power kW/HP	Gearbox	Speeds FWD/REV	Quick reverser	Clutch	Brakes	Differential	PTO	Handlebars	Wheels	Safety devices
<b>328</b> PowerSafe®	HONDA GP160 V	Gasoline	Recoil	3,6 / 4,8	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Parking brake	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	4.00-8 4.0-10 6.5/80-12 Steel cage wheels Ø 43 cm	In compliance with the EN 709/A4 regulation
	HONDA GX200 V	Gasoline	Recoil	4,1 / 5,5										
	HONDA GX270 V	Gasoline	Recoil	6,3 / 8,6										
	KOHLER KD350 V	Diesel	Recoil	5,5 / 7,5										
<b>338</b> PowerSafe®	HONDA GX270 V	Gasoline	Recoil or electric	6,3 / 8,6	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Parking brake on the two wheels	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 43 cm	In compliance with the EN 709/A4 regulation
	HONDA GX340 V	Gasoline	Recoil	8 / 10,7										
	KOHLER KD350 V	Diesel	Recoil or electric	5,5 / 7,5										
<b>340</b> PowerSafe®	HONDA GX390 V	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Independent work brake on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 regulation
	YANMAR LV100	Diesel	Recoil or electric	7,5 / 10										
<b>360</b> PowerSafe®	HONDA GX390 V	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Independent work brake on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	6.5/80-12 Steel cage wheels Ø 58 cm	In compliance with the EN 709/A4 regulation
	KOHLER KD440 V	Diesel	Recoil or electric	8 / 10,5										
<b>370<sup>HY</sup></b> PowerSafe®	HONDA GX390 V	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	2-speed ranges (slow/fast) in both FWD and REV	By hydrostatic unit	PowerSafe®, hydraulic with manual control	Independent work brake on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 regulation
	YANMAR LV100	Diesel	Recoil or electric	7,5 / 10										